

MAK PU PRIMER

Polymerized Antiroot Primer For Polyurethane Coatings



Description

MAK PU Primer is a tar extended single pack, moisture cure polyurethane coating primer and sealer, with excellent penetrating properties. MAK PU Primer is a single component adhesion promoter primer and sealer for use where toughness, chemical resistance, fast curing, and printability are required. MAK PU Primer bonds to and seals concrete, metal and timber, rubber, PVC, urethane and cured epoxies. It is slightly thixotropic in nature and has anti root properties.

Features

- Excellent Adhesion
- Fast Curing
- Chemical Resistant
- Multipurpose
- Waterproof and anti-root

Area of Application

 Priming concrete, wood, rubber, etc. for fiberglass, PVC and polyurethane application.

Sealing porous surfaces.

Directions For Use

- Surface Preparation: Concrete surfaces must be cured for at least 28 days
- Surface must be dry and free of grease, oils and other contaminants.
- Large areas can be coated using a rubber squeegee.

Apply quickly and liberally by good quality brush, roller or squeegee. MAK PU Primer may be also sprayed.

If two coats of PU Primer are required, apply within 4-16 hours, however ensure the first coat has sufficiently hardened to avoid lifting of the coating.

Coverage

Apply minimum 400 gms/sqm of Mak PU Primer for dry film thickness of approx. 300 micron.

Packaging

MAK PU Primer is packed 20 Ltr. drums.



MAK PU PRIMER

Polymerized Antiroot Primer For Polyurethane Coatings

Ceneral PropertiesColourBlackCure Time30-60 minService Temperature-150 C to +700 CShelf Life12 monthsChemical resistanceGood

M.K. PETRO PRODUCTS INDIA PVT. LTD

[AN ISO 9001 Certified Company] Village Mujeri Road, Ballabhgarh, Faridabad Ph: +91-9560096816 Toll-free: 1800-103-9664 Website: www.makphalt.com Email: info@makphalt.com

