

MAK CRACK-O-FILL

MODIFIED CRACK AND VOID FILLER

Description

MAK CRACK-O-FILL is a single component modified cement based filler material to be used for filling of cracks/ Voids and making covings before waterproofing treatments.

Area of Applications

- ◆ To seal crack up to 5-10 mm wide.
- ◆ To make coving on all junctions.

Key Features

- ◆ Single component. easy to use.
- ◆ Non - shrink.
- ◆ Economical.
- ◆ High bond strength.

Packing

MAK CRACK-O- FILL is available in 1kg and 25 kg packs.

Technical

Form : Powder

Colour : GREY / WHITE

M.K. PETRO PRODUCTS INDIA PVT. LTD

[AN ISO 9001 Certified Company]

Village Mujeri Road, Ballabhgarh, Faridabad

Ph: +91-9560096816

Toll-free: 1800-103-9664

Website: www.makphalt.com

Email: info@makphalt.com



Application Procedure

Add 25 kg of MAK CRACK-O- FILL with 7-8 ltrs of water and make it in dough form. It should be mixed properly so there are no lumps in it. Open all cracks to be filled, in V groove, pre dampen the surface of crack and then fill it with the mixed MAK CRACK-O- FILL.

For covings also the same method, of pre dampening and then placing mixed MAK CRACK-O- FILL on the area, could be done.

Storage

Store under cover, out of direct sunlight and protect from extremes of temperature. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging.

Disclaimer

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

