

MAK POLY PRIMER

Special Polymerized Primer For
Polysulphide Sealant

Description

MAK Poly Primer is a clear, single pack, moisture cure polyurethane coating, with excellent penetrating properties.

MAK Poly Primer is a single component adhesion promoter primer and sealer for use where toughness, chemical resistance, fast curing, and printability are required.

MAK Poly Primer bonds to and seals concrete, metal and timber, rubber, PVC, urethane, polysulphides and cured epoxies.

Features

- ◆ Excellent Adhesion
- ◆ Fast Curing
- ◆ Chemical Resistant
- ◆ Multipurpose

General Properties

- ◆ **Colour:** Transparent
- ◆ **Cure Time:** 30-60 min
- ◆ **Service Temperature:** -15° C to +70° C
- ◆ **Shelf Life:** 12 months
- ◆ **Chemical resistance:** Excellent

Packaging

MAK Poly Primer is packed 20 Ltr. drums.

M.K. PETRO PRODUCTS INDIA PVT. LTD

[AN ISO 9001 Certified Company]

Village Mujeri Road, Ballabgarh, Faridabad

Ph: +91-9560096816

Toll-free: 1800-103-9664

Website: www.makphalt.com

Email: info@makphalt.com



Areas of Application

- ◆ Priming concrete, wood, rubber, etc. for fiberglass, PVC, polysulphide and polyurethane application
- ◆ Sealing porous surfaces

Coverage

1 LTR MAK Poly Primer = 6-8 sqm per coat
(depending on surface roughness)

Directions For Use

- ◆ **Surface Preparation:** Concrete surfaces must be cured for at least 28 days.
- ◆ Surface must be dry and free of grease, oils and other contaminants.
- ◆ Large areas can be coated using a rubber squeegee.
- ◆ Apply quickly and liberally by good quality brush, roller or squeegee. MAK Poly Primer may be also sprayed.

If two coats of Poly Primer are required, apply within 4-16 hours, however ensure the first coat has sufficiently hardened to avoid lifting of the coating.

